

**LED LINEAR FOCUS**    **Product code GT. RH-W21 (add suffix see below)**

**DESCRIPTION /**                      Continuous Linear LED ceiling fixture, surface mounted, adjustable. Dimmable

**WHY USE THIS:**                      Seamless lines with focused lenses for washing ceiling, wall & facades.  
Supplied with connections for linking.




Remote Driver 24v DC

Shown with optional anti-glare guard

IP66 zone 1    **CE**    **LED**    IEE : A+    EN 60598.

Dimensions (mm)
L1000 / 500 / 300 x W28 x H74mm
Cut-out (mm)
N/A



L=1000 / 500 / 300mm

<b>material light fixture</b>	Aluminium & steel
<b>colours &amp; finish/ (suffix)</b>	Black -10,    Aluminium, RAL - xxxx
<b>light source &amp; voltage options</b> (PLEASE CONTACT US FOR ALTERNATIVE SOURCES)	a) Asymmetric 12x45 Deg 18W/m LED (1500 lms/m) 24v b) 60 Deg 18W/m LED (1500 lms/m) 24v c) 90 Deg 18W/m LED (1500 lms/m) 24v d)
<b>colour temperature /(suffix)</b>	<b>2700K/ 3000K / 4000K / (5000K / DMX to order)</b>
<b>CRI (colour render) /(suffix)</b>	85
<b>MacAdam</b>	<3
<b>Controls options /(suffix)</b>	PHASE DIMMING DALI / DMX 0-10v
<b>Optional Accessories</b>	
<b>AV. Weight (kg)</b>	2 per metre
<b>Emergency Available?</b>	No
<b>Special Notes</b>	<b>Remote driver</b> <b>Supplied with in &amp; out connections (male / female)</b>

**technical performance**



contact Glow-tech for all .ies files    **OSRAM** Opto Semiconductors